



## GLAND SEAL WATER REQUIREMENTS



Pump Size	Model	Standard Full Flush Arrangement		Inches	FLOWSETTER-WATER REDUCTION VALVE	Total Net Price
		USGPM	Litres/min			
2x2-10	SRL	1	4	3/8"	Model AM – Circuit Sentry™ Flo-Setter – Externally Adjustable Balance and Commissioning Valve with Supplied Ball Isolation/Shut Off Valve, Two Pressure / Temperature Ports, Tailpiece, and Union End. Sized for <b>2 GPM PART NUMBER: 2AMFGSRL</b> Inlet: 1/2" NPTM Outlet: 1/2" NPTF. <b>Flow Range: 0.18 to 4.85gpm</b>	Contact Us
3x3-10	SRL SRL-C	2	8	3/8"		
5x4-14	SRL	4	15	3/8"	Model AM – Circuit Sentry™ Flo-Setter – Externally Adjustable Balance and Commissioning Valve with Supplied Ball Isolation/Shut Off Valve, Two Pressure / Temperature Ports, Tailpiece, and Union End. Sized for <b>4 GPM PART NUMBER: 4AMFGSRL</b> Inlet: 3/4" NPTM Outlet: 3/4" NPTF. <b>Flow Range: 0.31 to 8.15gpm</b>	Contact Us
6x6-15	SRL	6	23	3/8"		
8x6-18	SRL-C	9	34	3/8"	Model AM – Circuit Sentry™ Flo-Setter – Externally Adjustable Balance and Commissioning Valve with Supplied Ball Isolation/Shut Off Valve, Two Pressure / Temperature Ports, Tailpiece, and Union End. Sized for <b>8 GPM PART NUMBER: 8AMFGSRL</b> Inlet: 1" NPTM Outlet: 1" NPTF. <b>Flow Range: 0.44 to 10.35gpm</b>	Contact Us
6x6-21	SRL-XT	12	45	1/2"	Model AM – Circuit Sentry™ Flo-Setter – Externally Adjustable Balance and Commissioning Valve with Supplied Ball Isolation/Shut Off Valve, Two Pressure / Temperature Ports, Tailpiece, and Union End. Sized for <b>12 GPM PART NUMBER: 12AMFGSRL</b> Inlet: 1-1/4" NPTM Outlet: 1-1/4" NPTF. <b>Flow Range: 0.88 to 21.13gpm</b>	Contact Us
10x8-21	SRL-C					
8x8-25	SRL-XT	14	53	1/2"		
12-10-25	SRL-C					
10x10-28	SRL-XT	16	61	1/2"	Model AM – Circuit Sentry™ Flo-Setter – Externally Adjustable Balance and Commissioning Valve with Supplied Ball Isolation/Shut Off Valve, Two Pressure / Temperature Ports, Tailpiece, and Union End. Sized for <b>20 GPM PART NUMBER: 20AMFGSRL</b> Inlet: 1-1/2" NPTM Outlet: 1-1/2" NPTF. <b>Flow Range: 1.76 to 32.76gpm</b>	Contact Us
14x12-29	SRL-C					
14x12-36	SRL-XT	20	76	1/2"		
16x14-34	SRL-C					
20x18-40	SRL-C	25	95	1/2"		